















#### LINEAR FLUORESCENT RETROFIT LAMP

For: T8 and T12 lamp replacement

The Energy Focus 300D Series LED Tube utilizes a direct-wire installation mode. Direct-wire TLEDs require that any existing ballast be removed and the TLED be rewired to operate on AC line voltage. Simple re-wiring and replacement of non-shunted lamp holders are also required. By removing the ballast your TLED no longer depends on any additional hardware to function normally and also minimizes points of failure - less maintenance required. In addition, the 300D Series provides 130 lm/W efficacy.

#### **FEATURES AND BENEFITS**

- Flicker-free LED lighting
- Non-shunted lamp holder required
- Integrated driver, Type-B (Direct-Wire)
- Replacement of existing tombstones recommended when retrofitting
- Single-ended power; INPUT end is electrically connected, other end has no internal connections.



Must use non-shunted lamp holders

For more information please see Accessories section.

©2020 Energy Focus, Inc. All Rights Reserved. Energy Focus, Inc. reserves the right to change specifications for product improvement without prior notice



# PRODUCT SPECIFICATIONS

Length	2' and 4' versions. Meets ANSI standards				
Body	Oval extruded aluminum				
Lens	Polycarbonate lens				
Connection	Medium bi-pin (G13) end cap				
Input Voltage	100-277vac, 50/60hz				
Driver	Single end power; integrated LED driver				
Available colors	3500K 4000K 5000K				
CRI	>80				
Dimming	Non-dimmable				
Dimming Lifetime	Non-dimmable  L70 ≥60,000 hours				
Lifetime	L70 ≥60,000 hours				
Lifetime  Warranty  Environmental	L70 ≥60,000 hours  10-year warranty  Operating temp: -20° to 50°C Storage temp: -30° to 60°C Working humidity: 30% to 85% Storage humidity: 10% to 90%				







## PRODUCT SPECIFICATION

PART NUMBER	SIZE NOMINAL	POWER	LUMINOUS FLUX	UL PART NUMBER	DLC FAMILY
LEDFLT8-8 <b>XX</b> -208-228F	(24") 2'	8W	1040lm	3AJ810086	YYYBSA
LEDFLT8-8 <b>XX</b> -208-228C	(24") 2'	8W	1040lm	3AJ810086	YYYBSA
LEDFLT8-8 <b>XX</b> -413-338F	(48") 4'	13W	1690lm	3AJ81013635	YYYBSB
LEDFLT8-8 <b>XX</b> -413-338C	(48") 4'	13W	1690lm	3AJ81013635	YYYBSB
LEDFLT8-8 <b>XX</b> -418-388F	(48") 4'	18W	2340lm	3AJ810186	WWWBMZ
LEDFLT8-8 <b>XX</b> -418-388C	(48") 4'	18W	2340lm	3AJ810186	XXXXRF


*BUY AMERICAN P/N	SIZE NOMINAL	POWER	LUMINOUS FLUX	UL PART NUMBER	DLC FAMILY
LEDFLT8-8 <b>XX</b> -208-2B2F	(24") 2'	8W	1040lm	3AJ810086	YYYBSA
LEDFLT8-8 <b>XX</b> -413-3B2F	(48") 4'	13W	1690lm	3AJ81013635	YYYBSB
LEDFLT8-8 <b>XX</b> -418-3B2F	(48") 4'	18W	2340lm	3AJ810186	WWWBMZ
LEDFLT8-8 <b>XX</b> -418-3B2C	(48") 4'	18W	2340lm	3AJ810186	NNNMIE

XX refers to the option for 3500K, 4000K or 5000K color temperature. (Replace XX with 35, 40 or 50 when selecting).

## **ACCESSORIES**

- Single lampholder, no wires (model no. LEDFLSLH-G13NS-SBOG)
- Pair of two (2) lampholders, one with 3' wires (Model no. LEDFLSLH- G13NS-SNETGW)
- Single lampholder, with 3' wires (Model no. LEDFLSLH-G13NS-SBOGW)

## LINE DIAGRAM



©2020 Energy Focus, Inc. All Rights Reserved. Energy Focus, Inc. reserves the right to change specifications for product improvement without prior notice.



<sup>\*</sup>Please contact our Customer Support Department (800-327-7877) for additional part number configurations.