



Vapor Tight LED Fixture

LED T8 FIXTURE

50" Vapor Tight LED Fixture provides IP65 rated, high-temperature proof and UV resistant protection - designed to function with Energy Focus lamps.

FEATURES AND BENEFITS


- Polycarbonate lens
- Designed for Energy Focus TLED lamps
- Silicone seal gasket and durable polycarbonate clip and hook assembly
- Durable IP65 Vapor-Tight housing ideal for installations requiring IP65. Such as parking garages, manufacturing areas, walkways, tunnels, and more

PRODUCT SPECIFICATIONS

Length	50" Fixture
Body	Bayer 2407 gray polycarbonate. Polycarbonate lens and metal lens latches. Silicone seal gasket and durable metal clip and hook assembly
Connection	T8 LED ready. Pre-wired, non-shunted lampholders included
Input Voltage	100-277vac, 50/60hz
Mounting	Stainless steel mounting brackets Plastic cable gland/hub
Dimming	Non-dimmable
Lifetime	5-year warranty
Attributes	IP65 rated, vapor-tight, non-corrosive, impact proof, high temperature proof and UV resistant
Optical System	Flat metal reflector



Non-shunted lamp holders included



PRODUCT SPECIFICATION

PART NUMBER	SIZE	FIXTURE L INCHES	FIXTURE W INCHES	FIXTURE H INCHES	COUNT
LEDF-T8VT-4-2	(48") 4'	50	6	4.2	2 lamps
LEDF-T8VT-4-3	(48") 4'	50	6	4.2	3 lamps

RECOMMENDED ENERGY FOCUS LAMPS

PART NUMBER	SIZE NOMINAL	UNITS	POWER	LUMINOUS FLUX	EFFICACY
LEDFLT8-840-418-388C	(48") 4'	2	36W	4680lm	130
LEDFLT8-840-418-388C	(48") 4'	3	54W	7020lm	130

LINE DIAGRAM

